# Safety Data Sheet FREE AEROSOL

Supercedes Date 10/17/2013 Issuing Date 03/04/2016

# 1. PRODUCT AND COMPANY IDENTIFICATION

Product Name FREE AEROSOL Recommended use Lubricant Information on Manufacturer CERTIFIED LABS, DIV. OF NCH CORP.

BOX 152170 IRVING, TEXAS 75015 Product Code 5C68
Chemical nature Solvent blend
Emergency Telephone Number
CHEMTREC® 800-424-9300
Telephone inquiry
972-579-2477

# 2. HAZARD IDENTIFICATION

Color Amber Physical state Liquid Odor Solvent

Category 1

Compressed Gas

Category 1

Category 2B

Category 3

Category 2

#### **GHS**

#### Classification

#### Physical Hazards

Flammable Aerosols Gases under pressure

Health Hazard

Aspiration Toxicity

Serious Eye Damage/Eye Irritation

Specific target organ systemic toxicity (single exposure) Specific target organ toxicity (repeated exposure)

Other hazards

None

#### Labeling Signal Word

DANGER



### Hazard statements

H222 - Extremely flammable aerosol

H280 - Contains gas under pressure; may explode if heated

H336 - May cause drowsiness or dizziness

H320 - Causes eye irritation

H304 - May be fatal if swallowed and enters airways

H373 - May cause damage to organs through prolonged or repeated exposure

### Precautionary Statements

P210 - Keep away from heat, sparks, open flames or hot surfaces.

P211 - Do not spray on an open flame or other ignition source

P251 - Pressurized container: Do not pierce or burn, even after use

P271 - Use in a well-ventilated area.

P260 - Do not breathe vapor, mist or gas

P264 - Wash face, hands and any exposed skin thoroughly after handling

 $\ensuremath{\mathsf{P270}}$  - Do not eat, drink or smoke when using this product.

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

P312 - Call a physician if unwell.

P337 + P313 - If eye irritation persists, get medical attention.

P304 + P340 - IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing.

P301+ P330 + P331 - IF SWALLOWED: Rinse mouth. DO NOT induce vomiting. Call a physician if unwell.

P233 - Keep container tightly closed

P410 + P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122

P403 - Store in a well-ventilated place

P501 - Dispose of contents and container in accordance with applicable local regulations.

20 % of the mixture consists of ingredient(s) of unknown toxicity

#### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Component	CAS No.	Weight % *
Petroleum distillates, hydrotreated light	64742-47-8	37.96722
Petroleum distillates, hydrotreated light naphthenic (<3% DMSO extractable)	64742-53-6	19.79802
Ethyl acetate	141-78-6	13.5
Solvent naphtha (petroleum), medium aliphatic	64742-88-7	8.7201
Sodium sulfonate	68608-26-4	5.58
Isobutane	75-28-5	5.449
Propane	74-98-6	4.551
Petroleum distillates, solvent dewaxed heavy paraffinic (<3% DMSO extractable)	64742-65-0	2.97
Nonane	111-84-2	0.9179
Water, distilled, conductivity or of similar purity	7732-18-5	0.45
Molybdenum, bis[O,O-bis(2-ethylhexyl) phosphorodithioato-S,S]dioxodi- .muthioxodi-, (Mo-Mo)	72030-25-2	0.07425
Petroleum distillates, hydrotreated heavy naphthenic (<3% DMSO extractable)	64742-52-5	0.02475

<sup>\*</sup>The exact percentage (concentration) of composition has been withheld as a trade secret

#### 4. FIRST AID MEASURES

**General advice** Avoid breathing vapors, mist, or gas. Avoid contact with skin, eyes and clothing.

Eye Contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue

flushing for at least 15 minutes. Get medical attention immediately.

Skin Contact Wash off with soap and plenty of water. Get medical attention if irritation develops and persists.

Inhalation If inhaled, remove to fresh air. Get medical attention if symptoms occur.

Ingestion Drink 1 or 2 glasses of water. Do NOT induce vomiting. Get medical attention immediately. Never

give anything by mouth to an unconscious person.

Notes to physician Aspiration hazard if swallowed - can enter lungs and cause damage. May be fatal if swallowed and

enters airways.

### 5. FIRE-FIGHTING MEASURES

Flash Point > 81 °F / > 27 °C Method Seta closed cup

Flammability Limits in Air %: Solvent mixture. Upper: 11.5 Lower: 1.9

Suitable Extinguishing Media

Water spray. Carbon dioxide (CO2). Foam. Dry chemical. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

### Specific hazards arising from the chemical

Solvent vapors are heavier than air and may spread along floors. Vapors may ignite and explode. Flame extension: >24 inches / >61 cm and Burnback: 3 inch / 7.5 cm. Material can create slippery conditions.

#### **Protective Equipment and Precautions for Firefighters**

As in any fire, we ar self-contained breathing apparatus pressure-demand, NOHSC (approved or equivalent) and full protective gear.

Aerosol Level (NFPA 30B) - 3

NFPA Health 2 Flammability 4 Instability 0
HMIS Health 2 Flammability 4 Instability 0

### 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions Use personal protective equipment. Remove all sources of ignition. Ensure adequate

ventilation. Prevent further leakage or spillage if safe to do so. Material can create slippery

conditions.

**Environmental Precautions** Do not flush into surface water or sanitary sewer system.

Methods for Containment Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth,

diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national

regulations (see section 13).

Methods for Cleaning Up

Use clean non-sparking tools to collect absorbed material. Pick up and transfer to properly labeled

containers.

Neutralizing Agent Not applicable.

## 7. HANDLING AND STORAGE

Handling Keep away from heat and sources of ignition. Avoid breathing vapors, mist or gas. Avoid contact with

skin, eyes and clothing.

Storage Keep away from open flames, hot surfaces and sources of ignition. Store in original container. Keep

containers tightly closed in a dry, cool and well-ventilated place.

#### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

**Exposure Guidelines** 

Component	ACGIH TLV	OSHA PEL	NIOSH
Petroleum distillates, hydrotreated light	525 mg/m <sup>3</sup> TWA	No data available	No data available
Petroleum distillates, hydrotreated light naphthenic (<3% DMSO extractable)	5 mg/m <sup>3</sup> as oil mist	10 mg/m <sup>3</sup> as oil mist	No data available
Ethyl acetate	TWA: 400 ppm	TWA: 400 ppm TWA: 1400 mg/m <sup>3</sup>	2000 ppm TWA: 400 ppm TWA: 1400 mg/m <sup>3</sup>
Isobutane	STEL: 1000 ppm	No data available	TWA: 800 ppm TWA: 1900 mg/m <sup>3</sup>
Propane	TWA: 1000 ppm	TWA: 1000 ppm TWA: 1800 mg/m <sup>3</sup>	2100 ppm TWA: 1000 ppm TWA: 1800 mg/m <sup>3</sup>
Petroleum distillates, solvent dewaxed heavy paraffinic (<3% DMSO extractable)	TWA: 5 mg/m <sup>3</sup> STEL: 10 mg/m <sup>3</sup>	TWA: 5 mg/m <sup>3</sup>	No data available
Nonane	TWA: 200 ppm	No data available	TWA: 200 ppm TWA: 1050 mg/m <sup>3</sup>
Molybdenum, bis[O,O-bis(2-ethylhexyl) phosphorodithioato-S,S]dioxodimuthioxodi-, (Mo-Mo)	TWA: 0.5 mg/m <sup>3</sup>	TWA: 5 mg/m <sup>3</sup>	No data available
Petroleum distillates, hydrotreated heavy naphthenic (<3% DMSO extractable)	TWA: 5 mg/m <sup>3</sup> ; STEL: 10 mg/m <sup>3</sup>	TWA: 5 mg/m <sup>3</sup>	No data available

**Engineering Measures** 

Ensure adequate ventilation, especially in confined areas. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction.

**Personal Protective Equipment** 

Eye/Face Protection Skin Protection Respiratory Protection Safety glasses with side-shields.

Wear suitable protective clothing, Impervious gloves.

In case of insufficient ventilation wear suitable respiratory equipment. When workers are facing  $% \left( 1\right) =\left( 1\right) \left( 1\right$ 

concentrations above the exposure limit they must use appropriate certified respirators.

**General Hygiene Considerations** 

Ensure that eyewash stations and safety showers are close to the workstation location. Remove

and wash contaminated clothing before re-use.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical stateLiquidViscosityNon viscousColorAmberOdorSolvent

Odor ThresholdNot applicableAppearanceTransparent - HazypHNot applicableSpecific Gravity0.797

 pH
 Not applicable
 Specific Gravity
 0.797

 Evaporation Rate
 19.12 (Butyl acetate=1)
 Percent Volatile (Volume)
 75.2

 VOC Content (%)
 41.90
 VOC Content (g/L)
 333.9

 Vapor Pressure
 1546.78 mmHg @ 70 °F
 Vapor Density
 1.4

n-Octanol/Water Partition Solubility Negligible No data available Melting Point/Range **Decomposition Temperature** No data available No data available **Boiling Point/Range** Flammability (solid, gas) No data available > 160 °F / 71 °C Flash Point > 81 °F / > 27 °C Method Seta closed cup

**Autoignition Temperature** No information available.

Flammability Limits in Air %: Solvent mixture Upper: 11.5 Lower: 1.9

## 10. STABILITY AND REACTIVITY

Chemical StabilityStable. Hazardous polymerization does not occur.Conditions to AvoidKeep away from open flames, hot surfaces, and sources of ignition.

Incompatible Products
Strong oxidizing agents, Reducing agents, Strong acids, Strong bases, Amines, Nitric acid.

Decomposition Temperature No data available

Hazardous Decomposition Products

Carbon oxides, Nitrogen oxides (NOx), Sulfur oxides, Aldehydes, Ketones, Hydrocarbons.

Possibility of Hazardous Reactions

None under normal processing.

# 11. TOXICOLOGICAL INFORMATION

Product Information No information available.

The following values are calculated based on chapter 3.1 of the GHS document

Dermal LD50 No information available

Inhalation LC50

Gas No information available
Mist No information available
Vapor No information available

Principle Route of Exposure Primary Routes of Entry Inhalation, Skin contact, Eye contact.

Skin contact, Skin Absorption.

**Acute Effects:** 

**Eyes** Causes eye irritation.

**Skin** Repeated exposure may cause skin dryness or cracking.

**Inhalation** May cause irritation of respiratory tract. Inhalation may cause central nervous system effects. May

cause central nervous system depression. Symptoms and signs include headache, dizziness,

fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Aspiration hazard if swallowed - can enter lungs and cause damage. May be fatal if swallowed and enters airways.

swallowed - can enter lungs and cause damage. May be fatal if swallowed and enters airways. Repeated and prolonged exposure to solvents may cause brain and nervous system damage.

Target Organ Effects
Aggravated Medical Conditions

Central nervous system, Respiratory system, Skin, Eyes.

Component Information

Respiratory system, Skin disorders, Neurological disorders.

**Acute Toxicity** 

Ingestion

**Chronic Toxicity** 

Component	Oral LD50	Dermal LD50	Inhalation LC50	Draize Test	Other
Petroleum distillates, hydrotreated light 64742-47-8	> 5000 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	no data available	no data available	no data available
Ethyl acetate 141-78-6	= 5620 mg/kg ( Rat )	> 18000 mg/kg ( Rabbit )	no data available	no data available	no data available
Solvent naphtha (petroleum), medium aliphatic 64742-88-7	> 5000 mg/kg ( Rat )	= 3000 mg/kg ( Rabbit )	> 5.28 mg/L ( Rat ) 4 h	no data available	no data available
Isobutane 75-28-5	no data available	no data available	= 658 mg/L ( Rat ) 4 h	no data available	no data available
Propane 74-98-6	no data available	no data available	= 658 mg/L ( Rat ) 4 h	no data available	no data available
Petroleum distillates, solvent dewaxed heavy paraffinic (<3% DMSO extractable) 64742-65-0	>5000 mg/kg (rat)	>5000 mg/kg (rabbit)	no data available	no data available	no data available
Nonane 111-84-2	no data available	no data available	= 3200 ppm ( Rat ) 4 h	no data available	no data available
Nater, distilled, conductivity or of similar purity 7732-18-5	> 90 mL/kg ( Rat )	no data available	no data available	no data available	no data available
Petroleum distillates, nydrotreated heavy naphthenic (<3% DMSO extractable) 64742-52-5	> 5000 mg/kg ( Rat )	> 5000 mg/kg (Rabbit)	no data available	no data available	no data available

Component	Mutagenicity	Sensitization	Developmental Toxicity	Reproductive Toxicity	Target Organ Effects
Ethyl acetate 141-78-6	no data available	no data available	no data available	no data available	Skin Eyes Respiratory system
Isobutane 75-28-5	no data available	no data available	no data available	no data available	Central nervous system
Propane 74-98-6	no data available	no data available	no data available	no data available	Central nervous system
Nonane 111-84-2	no data available	no data available	no data available	no data available	Skin Central nervous system Eyes Respiratory system
Molybdenum, bis[O,O-bis(2-ethylhexyl) phosphorodithioato- S,S]dioxodimuthioxodi-, (Mo-Mo)	no data available	no data available	no data available	no data available	Blood Eyes Respiratory system Kidney
72030-25-2					

Carcinogenicity

There are no known carcinogenic chemicals in this product.

### 12. ECOLOGICAL INFORMATION

Product Information Component Information

No information available.

Component	Toxicity to Algae	Toxicity to Fish	Microtox	Crustacea	log Pow
Petroleum distillates, hydrotreated light	No information available.	LC50 = 45 mg/L Pimephales promelas 96 h LC50 = 2.2 mg/L Lepomis macrochirus 96 h LC50 = 2.4 mg/L Oncorhynchus mykiss 96 h	No information available	No information available.	N/A
Petroleum distillates, hydrotreated light naphthenic (<3% DMSO extractable)	No information available.	LC50 > 5000 mg/L Oncorhynchus mykiss 96 h	No information available	1000: 48 h Daphnia magna mg/L EC50	N/A
Ethyl acetate	No information available.	LC50 = 484 mg/L Oncorhynchus	EC50 = 1500 mg/L 15 min EC50 = 5870 mg/L 15 min		0.6
Solvent naphtha (petroleum), medium aliphatic	EC50 = 450 mg/L Pseudokirchneriella subcapitata 96 h	LC50 = 800 mg/L Pimephales promelas 96 h	No information available	100: 48 h Daphnia magna mg/L EC50	N/A
Isobutane	No information available.	No information available.	No information available	No information available.	2.88
Propane	No information available.	No information available.	No information available	No information available.	2.3
Petroleum distillates, solvent dewaxed heavy paraffinic (<3% DMSO extractable)	No information available.	LC50 > 5000 mg/L Oncorhynchus mykiss 96 h	No information available	1000: 48 h Daphnia magna mg/L EC50	N/A
Petroleum distillates, hydrotreated heavy naphthenic (<3% DMSO extractable)	No information available.	LC50 > 5000 mg/L Oncorhynchus mykiss 96 h	No information available	1000: 48 h Daphnia magna mg/L EC50	N/A

Persistence and Degradability
Bioaccumulation
No information available.
No information available.
No information available.

# 13. DISPOSAL CONSIDERATIONS

**Product Disposal** Dispose of in accordance with local regulations.

Container Disposal Contents under pressure. Do not puncture. Empty remaining contents. Empty containers should be

taken for local recycling, recovery, or waste disposal.

# 14. TRANSPORT INFORMATION

DOT

Proper Shipping Name Consumer Commodity

Hazard Class ORM-D

**Description** Consumer Commodity, ORM-D

TDG

**Proper shipping name** Consumer Commodity

Hazard Class ORM-D UN-No UN1950

**Description** Consumer Commodity, ORM-D

ICAO

**UN-No** UN1950

**Proper Shipping Name** Aerosols, flammable

Hazard Class 2.1

**Shipping Description** UN1950, Aerosols, flammable, 2.1, LTD QTY

IATA

**UN-No** UN1950

Proper Shipping Name Aerosols, flammable

Hazard Class2.1ERG-Code126

Shipping Description UN1950, Aerosols, flammable, 2.1, LTD QTY

IMDG/IMO

Proper Shipping Name Aerosols, flammable

 Hazard Class
 2.1

 UN-No
 UN1950

 EmS No.
 F-A, S-A

**Description** UN1950, Aerosols, flammable,2.1,LTD QTY

# 15. REGULATORY INFORMATION

Inventories

TSCA Complies DSL Complies

**U.S. Federal Regulations** 

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazardous Categorization

Of III TO TITO TE TIME CITA COMO O	atogo::=atio::				
Acute Health Hazard	Chronic Health Hazard	Fire Hazard	Sudden R Pressure		Reactive Hazard
Yes	Yes	Yes	Ye		No
CERCLA					•
Comp	onent	Hazardous Substanc	es ROs	C	ERCLA EHS RQs

Component	Hazardous Substances RQs	CERCLA EHS RQs
Ethyl acetate	5000 lb	Not applicable

### 16. OTHER INFORMATION

 Prepared By
 Adrienne McKee

 Supercedes Date
 10/17/2013

 Issuing Date
 03/04/2016

Reason for RevisionNo information available.GlossaryNo information available.List of References.No information available.

CERTIFIED LABS, DIV. OF NCH CORP.assumes no responsibility for personal injury or property damage caused by the use, storage, or disposal of the product in a manner not recommended on the product label. Users assume all risks associated with such unrecommended use, storage or disposal of the product. The information provided on this document is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.